

# MV Power Station

Turnkey solution for large-scale PV plants

20-ft Standard Container / All-in-one / 2500–3125 kW



Max. PV Voltage up to 1500 V  
DC / AC Ratio up to 1.8



AGC / AVC, Night SVG Function  
LVRT / HVRT / FRT Function



Full Power Output under 50°C  
Support Outdoor Installation



Modular Design for Easy Maintenance  
Multiple DC Inputs



MODEL	GSM2500D-MV	GSM3125D-MV
<b>Input (DC)</b>		
Max. DC Input Voltage	1500 Vdc	
Min./Start Voltage	860 ~ 940 V (adjustable)	
MPPT Voltage Range	875 ~ 1300 V	
No. of MPPT	2	
No. of DC Input	Max. 18	
Max. DC Input Current <sup>1)</sup>	3207 A	4009 A
<b>Output (AC)</b>		
Rated AC Output Power	2500 kW	3125 kW
Max. AC Output Power	2750 kVA	3437 kVA
Inverter Max. Output Current	2646 A	3308 A
AC Output Voltage	10 ~ 35 kV	
Rated Grid Frequency	50 / 60 Hz	
AC Grid Frequency Range	45 ~ 55 / 55 ~ 65 (adjustable)	
Power Factor (cosΦ)	0.8 leading - 0.8 lagging	
THDi	< 3% (at nominal power)	
<b>Efficiency</b>		
Inverter Max. Efficiency	99.00%	
Inverter Euro Efficiency	98.70%	
<b>Transformer</b>		
Transformer Rated Power	2500 kVA	3125 kVA
Transformer Max. Power	2750 kVA	3437 kVA
LV / MV Voltage	0.6 kV / (10 ~ 35) kV	
Vector Group	Dy 11	
Cooling Type	ONAN	
Oil Type	Mineral Oil (PCB free)	
<b>Protection</b>		
DC Input Protection	Load Break Switch + Fuse	
Inverter AC Output Protection	Circuit Breaker	
AC MV Output Protection	Circuit Breaker	
Surge Protection	DC Type I+II; AC Type II	
Anti-islanding Protection	Yes	
Insulation Monitoring	Yes	
Leakage Current Monitoring	Yes	
Overheat Protection	Yes	
DC Reverse Polarity Protection	Yes	
AC Short-circuit Protection	Yes	
Anti-PID Function	Optional	
<b>General Specifications</b>		
Dimensions (W x H x D)	6058 x 2896 x 2438 mm	
Weight	13 t	
IP Class	Inverter IP55 / Others IP54	
Auxiliary Power Supply	10 kVA	
Operating Ambient Temperature Range	-40 ~ + 60°C	
Operating Relative Humidity Range	0 ~ 100% (non-condensing)	
Max. Operating Altitude	1000 m (Standard) / > 1000 m (Optional)	
Cooling Method	Forced Air Cooling	
Communication	IEC 104 Optical Fiber	
Display	Touch Screen	

1) Limited by software under DC input voltage of 875 V.